



▶ 2024

NEW PRODUCTS
MARSROCK



Wall-mounted AC EV Charger

7000W/11500W/22000W

Fast AC Charging.

Charge faster and more efficient

- Up to 32A, 400V, maximum power of 22KW
- Power adjustable by a switch or APP

More Reliability and Long-lasting

Built to last

- Evaluated and tested according to EU standards
- IK10 high impact resistance
- IP 55
- Capable of charging at full power between - 20°C~+55°C

Cloud Based Smart Charging

More convenience



● Product Specifications

Power	7KW	11.5KW	22KW
Voltage	AC 230V	AC 380V	AC 380V
Display	4" VA LCD(Default)		
	7"TFT Touch Screen(optional)		
Charging Mode	Smart charging		
Input/ Output Power Rating	Three-phase up to 22kW/32A		
And Current Input/Output Voltage	400V±20%, three-phase; 50Hz/60Hz		
Network Type	TT, TN		
Connector Type	IEC 62196 Type 2 or Type 1 plug, 5m		
	IEC 62196 Type 2 Socket or Socket with shutter		
Internal RCD	AC 30 mA, DC 6 mA		
Protection	Overcurrent, overvoltage, undervoltage, integrated surge protection		
Card Reader (Optional)	ISO 15693, ISO 14443		
Power Measurement Accuracy	+/- 1.0% from 1% to full scale		
WIFI/BT	Yes		
Connection Type	CASE C/CASE B		
APP	Yes		
Length Of Charging Gun Wire	5 meters		
Certification	CE		
OCPP	1.6J		
Case Material	Fireproof PC		
IP	IP55		
Operating Altitude	2000m		
Operating Temperature Range	- 20 °C~ + 55 °C		
Storage Temperature Range	- 20 °C~ + 85 °C		
Mounting	Wall- mounted or Pedestal		
Dimensions (HxWxD)	405*220*95mm		
Status Indication	LCD/APP (Optional, 4 inch LCD,)		
User Interface	Easy Charge APP; Easy Charge Cloud		
Connectivity	Bluetooth, Wi-Fi, Ethernet, 4G (Optional),RS485 for energy meter connection		
Communication Protocols	OCPP 1.6J		
User Authentication	APP, RFID card		
Software Update	OTA		
Safety And Compliance	IEC/EN 61851-1, IEC/EN 61851-21-2, IEC/EN62196		
Certification	CE		
Warranty	24 months, warranty extension possible		

MARS ROCK

Xiamen, P.R China



Tel: +86 5922237280
Mob: +86 18059289868
Web: www.marsrock.com.cn
marsrock@marsrock.com.cn